

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: Laminate Cleaner

Unique Formula Identifier (UFI): MKP0-F4KM-Y109-TUNJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Cleaner

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Guardian Protection Products A/S
Address: Knudevejen 22
Zip code: 6600
City: Vejen
Country: DENMARK
E-mail: guardian@guardian.dk
Phone: +45 75471767
Fax: +45 75471787

1.4. Emergency Telephone Number

Members of the public: 111 (NHS 111 (Scotland: NHS 24))

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Aerosol 1;H222 Aerosol 1;H229 Skin Sens. 1;H317 Eye Irrit. 2;H319 STOT SE 3;H336 Aquatic Chronic 3;H412

Most serious harmful effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system. Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Pictograms



Signal word: Danger

Contains

Substance: 1-methoxy-2-propanol; Naphtha (petroleum), hydrotreated heavy; Orange, sweet, ext.;

H-phrases

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

P-phrases

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P280	Wear protective gloves/eye protection.
P501	Dispose of contents/container in accordance with local regulation.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Assessment to determine PBT and vPvB has not been made.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
1-methoxy-2-propanol	107-98-2	203-539-1		25 - 40%		Flam. Liq. 3;H226 STOT SE 3;H336
ethanol	64-17-5	200-578-6		25 - 40%		Flam. Liq. 2;H225 Eye Irrit. 2;H319
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-151-9		25 - 40%	3	Flam. Liq. 3;H226 Asp. Tox. 1;H304 STOT SE 3;H336
Orange, sweet, ext.	8028-48-6	232-433-8		5 -< 10%	3	Flam. Liq. 3;H226 Asp. Tox. 1;H304 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411
Carbon dioxide	124-38-9	204-696-9		5 -< 10%		Press. Gas ref. liq. gas;H281
propan-2-ol	67-63-0	200-661-7		2.5 -< 5%		Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336

Please see section 16 for the full text of H-phrases.

3 = H304 is not applicable due to use as aerosols.

Ingredient comments: Pursuant to Regulation (EC) No. 648/2004 on detergents: 30% and more: aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
Skin contact:	Remove contaminated clothing. Wash skin with soap and water. Seek medical advice in case of persistent discomfort.
Eye contact:	Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice.
Burns:	Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.
General:	When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to eyes. Causes a burning sensation and tearing. Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. May cause sensitization by skin contact. Symptoms include reddening, swelling, blistering and ulceration - often slowly developing. The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system. Inhalation of spray mist may cause chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

The product decomposes when combusted and the following toxic gases can be formed: Carbon monoxide and carbon dioxide. CAUTION! Aerosol containers may explode.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with chemical resistant gloves.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stay upwind/keep distance from source. Wear safety goggles if there is a risk of eye splash. Wear gloves. Provide adequate ventilation. Smoking and naked flames prohibited.

For emergency responders: In addition to the above: Protective suit equivalent to EN 368, type 3, is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

6.3. Methods and material for containment and cleaning up

Wipe up drops and splashes with a cloth.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking and naked flames prohibited. Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work. Use the product under well-ventilated conditions.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not store with the following: Strong alkalis/ Strong acids/ Strong oxidisers/ Strong reducing agents.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Substance name	Time period	ppm	mg/m ³	fiber/cm ³	Comments	Remarks
1-methoxy-2-propanol	-	100	375			Sk
ethanol	-	1000	1920			
Naphtha (petroleum), hydrotreated heavy	-		1200			
Carbon dioxide	-	5000	9150			
propan-2-ol	-	400	999			

Sk = Can be absorbed through the skin.

Measuring methods:

Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

Legal basis:

EH40/2005 Workplace exposure limits. Last amended January 2020.

PNEC

ethanol, cas-no 64-17-5				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	0,96 mg/l			
PNEC aqua (marine water)	0,79 mg/l			
PNEC aqua (intermittent releases)	2,75 mg/l			
PNEC soil	0,63 mg/kg dw			

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

PNEC sediment (freshwater)	3,6 mg/kg			
PNEC STP (wastewater-treatment facilities)	580 mg/l			
PNEC sediment (marine water)	2,9 mg/kg dw			
Orange, sweet, ext., cas-no 8028-48-6				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC soil	0,261 mg/kg			
PNEC sediment (marine water)	0,13 mg/kg			
PNEC sediment (freshwater)	1,3 mg/kg			
PNEC STP (wastewater-treatment facilities)	2,1 mg/l			
PNEC aqua (intermittent releases)	5,77 µg/l			
PNEC aqua (marine water)	0,54 µg/l			
PNEC aqua (freshwater)	5,4 µg/l			
propan-2-ol, cas-no 67-63-0				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC sediment (marine water)	552 mg/kg			
PNEC aqua (freshwater)	140,9 mg/l			
PNEC soil	28 mg/kg			
PNEC aqua (marine water)	140,9 mg/l			
PNEC aqua (intermittent releases)	140,9 mg/l			
PNEC STP (wastewater-treatment facilities)	251 mg/l			
PNEC sediment (freshwater)	552 mg/kg			

DNEL - workers

ethanol, cas-no 64-17-5					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	343 mg/kg bw/day				
Inhalation DNEL (acute/short-term exposure - local effects)	1900 mg/m ³				
Inhalation DNEL (long-term exposure - systemic effects)	950 mg/m ³				
Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	300 mg/kg bw/day				

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Inhalation DNEL (long-term exposure - systemic effects)	1500 mg/m ³				
Orange, sweet, ext., cas-no 8028-48-6					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (acute/short-term exposure - local effects)	1858 mg/m ²				
Dermal DNEL (long-term exposure - systemic effects)	8,89 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	31,1 mg/m ³				
propan-2-ol, cas-no 67-63-0					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	888 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	500 mg/m ³				

DNEL - general population

ethanol, cas-no 64-17-5

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	206 mg/kg bw/day				
Inhalation DNEL (acute/short-term exposure - local effects)	950 mg/m ³				
Inhalation DNEL (long-term exposure - systemic effects)	114 mg/m ³				
Oral DNEL (long-term exposure - systemic effects)	87 mg/kg bw/day				

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	300 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	900 mg/m ³				
Oral DNEL (long-term exposure - systemic effects)	300 mg/kg bw/day				

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Orange, sweet, ext., cas-no 8028-48-6					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Oral DNEL (long-term exposure - systemic effects)	4,44 mg/kg bw/day				
Dermal DNEL (acute/short-term exposure - local effects)	929 mg/m ²				
Dermal DNEL (long-term exposure - systemic effects)	4,44 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	7,78 mg/m ³				
propan-2-ol, cas-no 67-63-0					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	319 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	89 mg/m ³				
Oral DNEL (long-term exposure - systemic effects)	26 mg/kg bw/day				

8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles. Eye protection must conform to EN 166.

Personal protective equipment, skin protection: Wear gloves. Type of material: Nitrile rubber. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374.

Personal protective equipment, respiratory protection: In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A. Respiratory protection must conform to one of the following standards: EN 136/140/145.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit	Remarks
State	Aerosol	
Colour	Clear	
Odour	No data	
Solubility	Solubility in water: Not miscible	
Explosive properties	No data	
Oxidising properties	No data	
pH (solution for use)	No data	

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

pH (concentrate)	No data	
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flash Point	46 °C	
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	No data	
Vapour pressure	No data	
Vapour density	No data	
Relative density	No data	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
Viscosity	No data	
Odour threshold	No data	

9.2. Other information

Other Information: None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Strong acids/ Strong alkalis/ Strong oxidisers/ Strong reducing agents.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid temperatures >50°C.

10.5. Incompatible materials

Strong acids/ Strong alkalis/ Strong oxidisers/ Strong reducing agents.

10.6. Hazardous decomposition products

The product decomposes when combusted or heated to high temperatures and the following toxic gases can be formed:
Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		10470mg/kg			

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000mg/kg			

Orange, sweet, ext., cas-no 8028-48-6

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		5000mg/kg			

propan-2-ol, cas-no 67-63-0

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		5840mg/kg			

Spray mist in mouth may irritate mucous membranes in mouth and throat. The product does not have to be classified. Test data are not available for all substances

Acute toxicity - dermal

ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 17100mg/kg			

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000mg/kg			

Orange, sweet, ext., cas-no 8028-48-6

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 5000mg/kg			

propan-2-ol, cas-no 67-63-0

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 2000mg/kg			

The product does not have to be classified. Test data are not available for all substances

Acute toxicity - inhalation

ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50		124.7mg/l			

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50		> 5mg/l			

Carbon dioxide, cas-no 124-38-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	0,5h	470000ppm			

propan-2-ol, cas-no 67-63-0

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4h	66.1mg/l			

The product does not have to be classified. Test data are not available for all substances

Skin corrosion/irritation:

Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. The product does not have to be classified. Test data are not available.

Serious eye damage/eye irritation:

Irritating to eyes. Causes a burning sensation and tearing.

Respiratory sensitisation or skin sensitisation:

May cause sensitization by skin contact. Symptoms include reddening, swelling, blistering and ulceration - often slowly developing.

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

- Germ cell mutagenicity:** The product does not have to be classified. Test data are not available.
- Carcinogenic properties:** The product does not have to be classified. Test data are not available.
- Reproductive toxicity:** The product does not have to be classified. Test data are not available.
- Single STOT exposure:** The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. Can be absorbed through the skin causing symptoms such as dizziness and headache. The product does not have to be classified. Test data are not available.
- Repeated STOT exposure:** Prolonged or repeated exposure by skin contact or inhalation of vapours may cause damage to the central nervous system. The product does not have to be classified. Test data are not available.
- Aspiration hazard:** Inhalation of spray mist may cause chemical pneumonia. The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.
- Other toxicological effects:** None known.

SECTION 12: Ecological information

12.1. Toxicity

ethanol, cas-no 64-17-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Name of species not specified		96hLC50	1100mg/l			
Crustacea	Name of species not specified		48hLC50	9268 - 14221mg/l			

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Name of species not specified		96hLC50	> 1000mg/l			
Crustacea	Name of species not specified		48hEC50	1000mg/kg			
Algae	Name of species not specified		EC	> 1000mg/l			

Orange, sweet, ext., cas-no 8028-48-6

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Name of species not specified		96hLC50	5.65mg/l			
Crustacea	Name of species not specified		48hEC50	1.1mg/l			
Algae	Name of species not specified		72hEC50	150mg/l			

propan-2-ol, cas-no 67-63-0

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
----------	---------	---------------	-----------	-------	------------	-------------	--------

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Fish	Name of species not specified		96hLC50	8970 - 9280mg/l			
Crustacea	Name of species not specified		24hEC50	9714mg/l			
Algae	Name of species not specified			> 1800mg/l			

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

ethanol, cas-no 64-17-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.		

Naphtha (petroleum), hydrotreated heavy, cas-no 64742-48-9

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.		

Orange, sweet, ext., cas-no 8028-48-6

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.		

propan-2-ol, cas-no 67-63-0

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.		

Expected to be biodegradable. Test data are not available for all substances

12.3. Bioaccumulative potential

Test data are not available for all substances

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

No assessment has been made.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Avoid unnecessary release to the environment.

Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility with the specifications set out below.

Aerosol sprays: EWC code: 16 05 04 Gases in pressure containers containing dangerous substances. Wiping cloths with organic solvents: EWC code: 15 02 02 Absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances.

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

SECTION 14: Transport information

Land transport (ADR/RID)

<p>14.1. UN number or ID number: 1950</p> <p>14.2. UN proper shipping name: AEROSOLS</p> <p>14.3. Transport hazard class(es): 2.1</p> <p>Hazard label(s): 2.1</p> <p>Hazard identification number:</p>	<p>14.4. Packing group:</p> <p>14.5. Environmental hazards: The product should not be labelled as an environmental hazard (symbol: fish and tree).</p> <p>Tunnel restriction code: D</p>
---	---

Inland water ways transport (ADN)

<p>14.1. UN number or ID number: 1950</p> <p>14.2. UN proper shipping name: AEROSOLS</p> <p>14.3. Transport hazard class(es): 2.1</p> <p>Hazard label(s): 2.1</p> <p>Transport in tank vessels: -</p>	<p>14.4. Packing group:</p> <p>14.5. Environmental hazards: The product should not be labelled as an environmental hazard (symbol: fish and tree).</p>
--	--

Sea transport (IMDG)

<p>14.1. UN number or ID number: 1950</p> <p>14.2. UN proper shipping name: AEROSOLS</p> <p>14.3. Transport hazard class(es): 2.1</p> <p>Hazard label(s): 2.1</p> <p>EmS: F-D, S-U</p>	<p>14.4. Packing group:</p> <p>14.5. Environmental hazards: The product is not a Marine Pollutant (MP).</p> <p>Environmental Hazardous Substance Name(s):</p> <p>IMDG Code segregation group: - None -</p>
---	--

Air transport (ICAO-TI / IATA-DGR)

<p>14.1. UN number or ID number: 1950</p> <p>14.2. UN proper shipping name: AEROSOLS, FLAMMABLE</p> <p>14.3. Transport hazard class(es): 2.1</p> <p>Hazard label(s): 2.1</p>	<p>14.4. Packing group:</p> <p>14.5. Environmental hazards: The product should not be labelled as an environmental hazard (symbol: fish and tree).</p>
--	--

14.6. Special precautions for user

None.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: Covered by: Regulation (EC) of the European Parliament and of the Council on detergents.

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

Council Directive (EC) on the protection of young people at work.

Directive 2012/18/EU (Seveso), P3a FLAMMABLE AEROSOLS: Column 2: 150 (net) t,
Column 3: 500 (net) t.

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.2.0	08/03/2021	Bureau Veritas HSE / THS	-

Abbreviations:
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: Very Persistent and Very Bioaccumulative
 STOT: Specific Target Organ Toxicity
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Training advice: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method: Calculation based on the hazards of the known components.

List of relevant H-statements

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H281	Contains refrigerated gas, may cause cryogenic burns or injury.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS is prepared by

Company: Bureau Veritas HSE Denmark A/S
 Address: Oldenborggade 25-31
 Zip code: 7000

Safety Data Sheet

Laminate Cleaner

Replaces date: 18/10/2019

Revision date: 08/03/2021
Version: 1.2.0

City: Fredericia
Country: DENMARK
E-mail: infohse@bureauveritas.com
Phone: +45 77 31 10 00
Homepage: <https://www.bvhse.dk/>

Document language: GB